

High visibility operator's station with heat, air conditioning and stereo making one-man operation possible

10' x 19' loading area produces 40" x 26" logs with a density of 30-80 lbs./cu. ft

4,000 lbs. lifting capacity at 20' reach.
25' 8" maximum reach.
Continuous grapple rotation

Lid cylinders have 8" bore x 29" stroke with 4" hardened chrome rods

6-cylinder John Deere or Cummins diesel engine

Kidney loop 5-micron filtration keeps hydraulic fluid cleaner for longer pump and valve life. Filter costs just \$150 to replace, not \$300



540° crane rotation

Ram cylinders have 12" bore and 129" or 88½" stroke. Hardened chrome on the 9" rods is almost 3 times thicker than others to resist scratches and cylinder wear

19' 2" L Box design chamber is made of Hardox® high-strength steel for lightness and strength

Produces a load of cars every 30 minutes (25 car bodies per hour) with Full Auto Cycle (ram in & out, doors open)

Reliable low-pressure double hydraulic pump is rated at 120 GPM at 2,100 RPM. Operates at 2,700 psi instead of 5,000 psi. Uses affordable, easily available lines and seals

Weighs 92,000 lbs. — light enough to be legally towable in all states

The Al-jon 580 Car Logger is built better, everywhere you look.



Get details today. • Al-jon Inc., 14599 2nd Avenue, Ottumwa, IA 52501 641-682-4506 or 800-255-6620 • www.aljon.com

KEEPING IT SIMPLE. BUILDING IT STRONG.

